

The BL 2500 is a 2.5mtr heavy duty laminator.

This laminator is easy to operate with the large push buttons on the control panel which is positioned on a long swing arm.

The machine is suitable for double side laminating with the 2 Combi winding positions on top and the 2 Combi winding positions at the bottom.

The tables can easily be pulled back or swung down or completely removed by hand for easy setup from material. The Autogrip shafts ensure an easy setup and positioning of a roll of material.



### Features:

- Industrial Design
- Controls on long swingarm
- Adjustable Nip pressure of the rollers

### Benefits:

- Heavy Duty Capable
- Easy Access to controls
- Control over laminating process

## Technical Specifications

### Weight

Unpacked: 1500 kg

### Dimensions

Depth (incl. front and rear table): 1300mm (51")  
Width: 3160mm (124,2")  
Height: 1985 mm (58,3")  
Table height (\*): 900 mm (35,4")  
(\* adjustable by the four height-adjustable machine supports)

### Voltage

230V, 50/60 Hz, 16A

### Maximum Speed

8 m/min (25,6 ft/min)

### Material limits for prints/panels

#### Lamination

Maximum width: 2500 mm (27,6")  
Maximum thickness laminator: 80 mm (1,97")

### Shaft capacities

Core: Ø76,2 mm (3")  
Max. unwind diameter: 300 mm (11,8")

### Noise level

less than 70 dB (A)

### Max. roller temperature

135°C

### Temperature reading

digital

### Pressure rollers

2

### Winding positions

1x unwind positions top  
1x windup position top

### Autogripshafts 3 Inch

2

### Available options

- Heatable top roller, up to 135°C
- Heatable bottom roller, up to 135°C
- Additional Winding positions bottom
- Wrinkle control for unwind position
- Ionisation bar
- Other options on request

Details are correct at the time of publication.

Crest Dutch Machinery B.V. reserves the right to alter specifications at any time.